



# Spatial Resolution Characterization for Aerial Digital Imagery

Slawomir Blonski, Kenton Ross, Mary Pagnutti  
*Science Systems and Applications, Inc.*

Thomas Stanley  
*NASA, Stennis Space Center*

## Acknowledgements


Robert E. Ryan, SSAI SSC  
Vicki Zanoni, NASA GSFC



# Spatial Characterization Approach

*Stennis Space Center*

- NASA and the U.S. Geological Survey (USGS) have jointly developed capability for characterization of aerial digital imagery:
  - USGS defines characterization requirements and interfaces with industry.
  - NASA performs characterizations of image products using the Stennis Space Center (SSC) test range.
- Analysis includes geopositional accuracy and spatial response:
  - Radiometric characterization is to be performed in the future.
- Spatial response is characterized based on measurements of Relative Edge Response (RER):
  - RER is one of the engineering parameters used in the General Image Quality Equation (GIQE) to provide predictions of imaging system performance expressed in terms of the National Imagery Interpretability Rating Scale (NIIRS).
- RER is estimated using the SSC edge targets and the tilted edge technique:
  - RER is a geometric mean of normalized edge response differences measured in two directions of image pixels (X and Y) at points distanced from the edge by -0.5 and 0.5 ground sample distance (GSD).




# SSC Edge Targets


Stennis Space Center




*Image of the SSC edge targets acquired by the QuickBird satellite (60 cm GSD)*




- Two pairs of edge targets painted on a concrete surface
- Orientation differs by 4 degrees to accommodate images with various pixel directions (Universal Transverse Mercator-projected and others)





# Tilted Edge Technique

Stennis Space Center




$\theta$  – edge tilt angle

$\delta$  – pixel index


$x$  – pixel's distance from edge (in GSD)

**Problem:** Digital cameras undersample edge target


**Solution:** Image tilted edge to improve sampling



3 examples of undersampled edge responses measured across the tilted edge




Superposition of 24 edge responses shifted to compensate for the tilt



# Relative Edge Response

Stennis Space Center

$$RER = \sqrt{[ER_X(0.5) - ER_X(-0.5)][ER_Y(0.5) - ER_Y(-0.5)]}$$




*RER estimates effective slope of the imaging system's edge response, because the distance between the points for which the differences are calculated is always equal to the GSD*



# Effects of RER on Civil NIIRS

Stennis Space Center


*NIIRS estimates based on GIQE  
(assuming no MTF compensation)*



*Identify large farm  
animals by type  
(e.g., horses, cows)  
(NIIRS 6.7)*

*Smaller RER can  
degrade  
interpretability,  
despite finer GSD*

*Detect individual large  
domesticated animals  
(e.g., horses, cattle) in  
grazing pastures  
(NIIRS 5.3)*



# Meaning of RER in Remote Sensing

Stennis Space Center

Radiance measured for each pixel is assumed to come from the Earth's surface area represented by that pixel. However, because of many factors, actual measurements integrate radiance  $L$  from the entire surface with a weighting function provided by a system's point spread function (PSF):

$$L_T = \int_{-\infty}^{\infty} \int_{-\infty}^{\infty} PSF(x, y) L(x, y) dx dy$$

Part of radiance that originates in the pixel area is given by:

$$L_P = \int_{-0.5}^{0.5} \int_{-0.5}^{0.5} PSF(x, y) L(x, y) dx dy$$




One can show that the Relative Edge Response squared ( $RER^2$ ) can be used to assess the percentage of the measured pixel radiance that actually originates from the Earth's surface area represented by the pixel:

$$L_P / L_T \approx RER^2$$

*A simple example:  
Box PSF  
Width = 2 GSD*

$$\begin{aligned} ER(0.5) - ER(-0.5) &= \\ 0.75 - 0.25 &= 0.50 \\ RER &= 0.50 \end{aligned}$$

*$RER^2 = 0.25$  means that 25% of information collected with the pixel PSF (blue square) comes from the actual pixel area (shadowed square)*






# Example: 15 cm GSD Panchromatic Image

Stennis Space Center

*Image area  
selected for the  
spatial resolution  
measurement in  
the Northing  
direction*



*Full edge response  
extracted from the  
selected area of the  
image*



*Central part of the  
edge response used  
to measure the RER  
difference*






# Example: 30 cm GSD Multispectral Image

Stennis Space Center


Section of the characterized image showing the SSC edge targets



5272-A\_TARGET.tif : Band 2



5272-A\_TARGET.tif : Band 2





# Spatial Characterization Results

Stennis Space Center

Image Acquisition Date	Sensor	Company	GSD (cm)	RER
22-Nov-2002	Leica ADS40	EarthData International®	25	0.5 (BW) 0.6 (IR) 0.5 (RGB)
24-Nov-2003	DAIS	Space Imaging® (GeoEye™)	50	0.7 (VNIR)
5-Dec-2003	IKONOS*	Space Imaging (GeoEye)	100	0.7 (pan)
18-Feb-2004	Z/I Imaging DMC	AERO-METRIC, INC.®	15	0.4 (pan)
8-Nov-2004	Z/I Imaging DMC	3001, Inc.®	15 30	0.5 (RGB), 0.4 (CIR) 0.6 (RGB), 0.5 (CIR)
23-Feb-2005	Z/I Imaging DMC	Florida Department of Transportation	30	0.6 (RGB)

*\*satellite*

*Reports with the characterization results have been  
delivered by NASA to USGS*

*GSD – Ground Sample Distance  
RER – Relative Edge Response  
BW – Black, White  
IR – Infrared  
RGB – Red, Green, Blue  
VNIR – Visible/Near Infrared  
CIR – Color Infrared*

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
<p>The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.</p> <p><b>PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.</b></p>					
1. REPORT DATE (DD-MM-YYYY) 16-03-2006		2. REPORT TYPE Conference Presentation		3. DATES COVERED (From - To) Jan. 2005-March 2006	
4. TITLE AND SUBTITLE Spatial Resolution Characterization for Aerial Digital Imagery				5a. CONTRACT NUMBER NASA Task Order NNS04AB54T	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
				5d. PROJECT NUMBER SWR C15C-JC15-00	
6. AUTHOR(S) Slawomir Blonski (1) Kenton Ross (1) Mary Pagnutti (1) Thomas Stanley (2)				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) (1) Science Systems and Applications, Inc., Bldg. 1105, John C. Stennis Space Center, MS 39529 (2) Applied Research & Technology Project Office, Code PA30, Bldg. 1100, John C. Stennis Space Center, MS 39529				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Applied Research & Technology Project Office, Code PA30, John C. Stennis Space Center, MS 39529				10. SPONSORING/MONITOR'S ACRONYM(S)	
				11. SPONSORING/MONITORING REPORT NUMBER SSTI-2220-0071 (R)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Unclassified/Publicly available STI per NASA Form 1676					
13. SUPPLEMENTARY NOTES Presentation for JACIE Civil Commercial Imagery Evaluation Workshop, March 14-16, 2006, U.S. Fish and Wildlife Service National Wildlife Visitors Center, Laurel, MD; sponsored by NASA/NGA/USGS; to be published in subsequent CD-ROM proceedings					
14. ABSTRACT <p>The U.S. Geological Survey (USGS) and the National Aeronautics and Space Administration have jointly conducted characterizations of aerial digital imagery from commercial data providers. In a typical scenario, a vendor acquired imagery over the Stennis Space Center (SSC) test range and provided a common data package to SSC. SSC personnel analyzed the geopositional accuracy and spatial resolution of the images, then documented the characterization results in a report and delivered the report to the USGS.</p> <p>Spatial resolution characterization was based on edge response measurements using one of the SSC edge targets and the tilted-edge technique. Relative Edge Response (RER) has been estimated for aerial digital imagery from several commercial data providers. RER is one of the engineering parameters used in the General Image Quality Equation to provide predictions of imaging system performance expressed in terms of the National Imagery Interpretability Rating Scale. RER also characterizes applicability of digital image products in quantitative remote sensing, such as thematic mapping based on image classification, because RER squared may be used to assess the percentage of the signal that actually originates from the Earth's surface area represented by the signal.</p>					
15. SUBJECT TERMS aerial digital imagery, geopositional accuracy, USGS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	b. ABSTRACT	c. THIS PAGE			Thomas Stanley
U	U	U	UU	10	19b. TELEPHONE NUMBER (Include area code) (228) 688-7779